



Film sealing and cutting unit equipped with a quick change system

Full color touch panel, mounted in a separate console close to the stretch hood

Horizontal and vertical stretching of film results in an excellent load stability and reduced film costs

The hood can be drawn below the bottom of a pallet to secure the load to the pallet

Different film reels can be placed, the Stretchhood automatically changes to the desired film reel

As a manufacturer of state-of-the-art packaging machines Willems Stretch Hooding BV offers an innovative, high quality and efficient solutions for your packaging on pallets.

Technical specifications:

Pallet dimensions: min. 800 x 600mm
 max. 1.600 x 1.200mm
 Load dimensions: 1.750 x 1.350mm
 Pallet positioning: ±10mm
 Maximum load: 1.500Kg
 Capacity: till 80 pallets per hour
 (depending on project specifications)
 Transport height: 500mm-600mm (standard 600mm)
 Power supply: 3x400V, 50Hz + Earth + "0"
 Diameter filmreel: max. 1.000mm

Load height: min. 400mm
 (incl. pallet) max. 3.500mm
 Load tolerance: offset max. 75mm

Transport speed: 12mtr/min.
 Installed power: 14 KW



Willems stretchhooder offers full protection against dirt, dust and moisture. The quality stretch hood film also protects your products against scratches and surface damage. Furthermore, the packaging machines deliver watertight hoods, in order to protect the value of your products.



Almost no maintenance required, the lifting and lowering of the stretch unit happens with toothed belts.



We guarantee the best possible protection for your pallets with our high quality stretchhood machine.



Multifunctional touch panel, easy operation by means of visualization of the operation of the stretchhooder.



The Hooder L stretchhood offers a cost-effective solution for a broad range of pallet packages.



Willems
 stretch hooding

Smaragdweg 20 • 5527 LB • Hapert • The Netherlands
 T: +31 (0) 497.64 40 55
 E: wbe@willemsbaling.eu W: www.willemonline.com